



Product Description

S-OIL SEVEN GOLD #9 A5/B5 is designed for improving fuel economy and contributing to lower CO2 emissions through low viscosity and friction property. And this ensures long oil life thanks to very pure synthetic base oil. This is suitable for the most stringent requirement of gasoline and diesel vehicles that required ACEA A5/B5, A1/B1 requirement.

Applications

- O Passenger cars with gasoline and diesel engine where ACEA A5/B5, A1/B1, API SL technical level is required
- O Suited to vehicles with DOHC, Turbocharger, Direct Injection System, Catalytic Converters

Features and Potential Benefits

- O Improved fuel efficiency by minimization of friction
- O Rapid oil flow in cold condition assures easy start, good drivability and reduction of fuel consumption during start of your engine
- O High viscosity index ensures adequate oil film strength at hot operating condition
- O Excellent oxidation and thermal stability provides reduced sludge formation and ensures long oil life
- O Excellent protection performance with optimized additive technology

Performance Level

O ACEA: A5/B5, A1/B1

O API: SL/CF O Ford: 913 C/D O Renault: RN 0700

Typical Properties

Test Items		Method	Unit	5W-30
Specific Gravity		ASTM D1298	-	0.856
Viscosity	40 °C	ASTM D445	cSt	58.2
	100 ℃	ASTM D445	cSt	10.0
Viscosity Index		ASTM D2270	-	159
Pour Point		ASTM D97	$^{\circ}$	L-40

S-OIL CORPORATION

192, Baekbeom-ro, Mapo-gu,

Seoul, 04196, Korea

S-OIL SEVEN GOLD #9 A5/B5 2019.06.20







This lubricant used recommended and for the application for which it has been designed does not present any particular risk. A material safety data sheet is obtainable via your commercial adviser.