



MULTI GRADE OIL FOR GASOLINE ENGINES

Product Description

S-OIL SEVEN RED #7 SJ is made by synthetic technology for all gasoline engines. It suitable for recent technology engines (multi valve, turbocharged, with/without catalytic converter) and vehicles requiring performance specification API SJ.

Applications

- O All gasoline engines, especially for most recent technology engines (multi valve, turbocharged, with/without catalytic converter) supercharged or not, in cars
- O Suitable for all journeys (in town, on highways) and particularly in severe conditions
- O For all driving styles, vigorous speeds in all seasons

Features and Potential Benefits

- O Meets API SJ and ILSAC GF-2 requirements, guarantee of an high and constant quality for lubricants
- O Ensures easy cold start due to its extreme fluidity at low temperature and maintains a very resistant oil film even at extremely high operating temperature
- O Gives the engine an excellent wear protection, develops performance and power
- O Keeps the engine's most sensitive parts clean thanks to its advanced detergent and dispersive additives

Performance Level

O API:SJ

O ILSAC: GF-2

Typical Properties

•			
t Items	Method	Unit	5W-30
	ASTM D1298	-	0.856
40 ℃	ASTM D445	cSt	64.6
100°C	ASTM D445	cSt	10.7
	ASTM D2270	-	157
	ASTM D92	°C	226
	ASTM D97	°C	-39
		ASTM D1298 40°C ASTM D445 100°C ASTM D445 ASTM D2270 ASTM D92	ASTM D1298 - 40°C ASTM D445 cSt 100°C ASTM D445 cSt ASTM D2270 - ASTM D92 °C

S-OIL CORPORATION

192, Baekbeom-ro, Mapo-gu,

Seoul, 04196, Korea

S-OIL SEVEN RED #7 SJ 2019.08.14



This lubricant used recommended and for the application for which it has been designed does not present any particular risk.

A material safety data sheet is obtainable via your commercial adviser.