



S-OIL SEVEN RED #9 LPG

FULLY SYNTHETIC LPG & GASOLINE ENGINE OIL

Product Description

S-OIL SEVEN RED #9 LPG is made by 100% synthetic base oil, suitable for all passenger cars that run on LPG and gasoline. Also suitable for latest engine fitted new technologies including turbocharger, DOHC, GDI and vehicles requiring performance specifications API SN, ILSAC GF-5.

Applications

- All passenger cars that run on LPG and gasoline
- Especially suitable for vehicles driving in modern start-stop traffic conditions
- Vehicles equipped with DOHC, Turbocharger, GDI are suggested to apply API SN, ILSAC GF-5 engine oil

Features and Potential Benefits

- This engine oil provides premium performance thanks to very stable and clean base oil properties
- High viscosity index ensures adequate oil film strength at hot operating condition
- S-OIL SEVEN RED #9 LPG is formulated with latest cleaning agents that help to remove dirt and deposits actively
- Eco-friendly engine oil with Improved fuel efficiency caused by minimization of friction in moving parts

Performance Level

- API : SN
- ILSAC : GF-5 (10W-30)

Typical Properties

| Test Items | Method | Unit | 10W-30 | 10W-40 | |
|------------------|------------|-----------|--------|--------|-------|
| Specific Gravity | ASTM D1298 | - | 0.855 | 0.859 | |
| Viscosity | 40°C | ASTM D445 | cSt | 64.7 | 90.4 |
| | 100°C | ASTM D445 | cSt | 10.21 | 13.60 |
| Viscosity Index | ASTM D2270 | - | 144 | 152 | |
| Flash Point | ASTM D92 | °C | 246 | 246 | |
| Pour Point | ASTM D97 | °C | -25 | -33 | |

S-OIL CORPORATION
192, Baekbeom-ro, Mapo-gu,
Seoul, 04196, Korea

S-OIL SEVEN RED #9 LPG
2019.06.20



This lubricant used recommended and for the application for which it has been designed does not present any particular risk.
A material safety data sheet is obtainable via your commercial adviser.