

Certificate of Analysis

PRODUCT : S-OIL 7 EV HYBRID 0W-20-EX (P4x4)

CERT. NO. : 20240425-0039

D A T E : 2024/04/25

CUSTOMER : S-OIL

TANK No. : IBT-04


DATE SAMPLED : 2024/04/01

LOT No. : 241084

TEST ITEMS	UNIT	TEST METHOD	RESULTS
Color		ASTM D 1500	L3.0
Density, 15	g/cm ³	ASTM D 4052	0.8466
Viscosity, 40	cSt	ASTM D 445	44.75
Viscosity, 100	cSt	ASTM D 445	8.451
Viscosity Index		ASTM D 2270	169
C.C.S., -35	cP	ASTM D 5293	5810
T.B.N	mgKOH/g	ASTM D 2896	7.39
Flash Point, COC		ASTM D 92	232
Pour Point		ASTM D 97	-45
Foaming Test Tendency/Stability, Sequence 1	ml	ASTM D 892	10/0
Foaming Test Tendency/Stability, Sequence 2	ml	ASTM D 892	20/0
Foaming Test Tendency/Stability, Sequence 3	ml	ASTM D 892	10/0

I CERTIFY THE ABOVE TEST RESULTS ARE TRUE AND CORRECT.

Chief Chemist
JB.Shin



S-OIL TotalEnergies Lubricants Co., Ltd.

Head Office : 16F, HSBC Building, 37, Chilpae-ro, Jung-gu, Seoul, Korea Tel.+82 2 6320 2000 Fax. +82 2 6320 2100
Plant : 436, Dangwol-ro, Onsan-eup, Ulju-gun, Ulsan, Korea Tel.+82 52 240 3133 Fax. +82 52 240 3134